




PCT/EP200 4 / 0 0 2 0 9 9

1.1 MAART 2004



INVESTOR IN PEOPLE




The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed


Dated 10 February 2004

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

An Executive Agency of the Department of Trade and Industry

Patents Form 1/77



The Patent Office

1/77

Patents Act 1977
(Rule 16)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form.)

1. Your reference

MBZ-0520

2. Patent application number

(The Patent Office will fill in this part)

0307920.9

-7 APR 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

MBT Holding AG
Vulkanstrasse 110
CH-8048 Zürich
Switzerland

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

7171101001
Switzerland

4. Title of the invention

SHRINKAGE REDUCING ADDITIVE

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Mr. P. Brown
FEB MBT
Albany House
Swinton Hall Road
Swinton
MANCHESTER M27 4DT

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

7178510001

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description

6

Claim(s)

4

Abstract

1

Drawing(s)

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents
(Please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

07.04.2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr. P. Brown, FEB MBT
(0161) 794 7411

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

SHRINKAGE REDUCING ADDITIVE

This invention relates to the prevention of shrinkage in cementitious compositions and to materials for achieving this.

5

A commonly-encountered problem with cementitious compositions such as concrete and mortar is their tendency to shrink on drying after placement. This can cause some cracking, the presence of which can not only be unsightly but which also can allow the penetration of water into the cementitious composition. This can degrade the concrete by, for example, freezing and thawing in winter conditions, or by allowing water and/or aggressive chemicals to reach steel reinforcing embedded in the concrete, causing corrosion and reducing durability.

The subject has been intensively studied and a large patent literature is evidence of the commonness of the problem and the desirability of solving it.

15

It has now been found that a particular class of materials can reduce substantially the drying shrinkage of cementitious compositions. The invention therefore provides a method of reducing the drying shrinkage of a cementitious composition to which water has been added and the composition placed, comprising adding to the composition prior to placement at least one siloxane compound that is at least one of liquid and soluble in at least one of water and aqueous alkali.


20

By "siloxane compound" is meant any siloxane-based material, that is, a material having a linear or branched siloxane backbone chain of the form $-\text{SiR}^a\text{R}^b-\text{O}-\text{SiR}^c\text{R}^d-\text{O}-$. Any such material will work in this invention, provided that it is liquid or at least slightly soluble in at least one of water and aqueous alkali.

25

Preferred siloxane compounds for use in this invention are selected from those that correspond to the general formula I:

30



where m and n are independently from 1-2000, preferably from 1-500 and more preferably from 1-200, a, b, and c are independently either 0 or 1 and X, Y and Z are selected from

-O-;

-O-(CH₂)₁₋₃₀-, this moiety being at least one of linear, branched and containing at least one ring;

-(CH₂)₁₋₃₀-, this moiety being at least one of linear, branched and containing at least one ring;

-CH₂-CH₂-CH₂-O-;

-CH₂-CH₂-CH₂-O-CH₂-CHOH-CH₂-;

-CH₂-CH₂-CH₂-O-CH₂-CHOH-CH₂-O-;

-CH₂-CH₂-CH₂-O-CH₂-CHOH-CH₂-N-;

and R, R' and R'' are independently selected from at least one of hydrogen, C₁₋₁₀₀ alkyl, C₆₋₃₀ aryl, C₇₋₃₀ aralkyl; C₇₋₃₀ alkaryl; C₁₋₃₀ hydroxyalkyl; C₃₋₂₀₀ polyhydroxyalkyl; polyether consisting of from 2-200 identical or different C₁₋₁₅ oxyalkylene units, with the proviso that, if there is present more than one type of oxyalkylene unit, there shall be present at least two of each unit; C₁₋₃₀ aminoalkyl; polyiminopolyalkylene having from 1-20 identical or different C₂₋₁₅ alkylene units; polyiminopolyoxyalkylene having from 1-20 identical or different C₂₋₁₅ oxyalkylene units; C₃₋₃₀ quaternary ammonium, optionally completely or partially ionised with at least one anion; C₄₋₃₀ betaine; carboxyl, optionally completely or partially ionised with any suitable cation; C₄₋₃₀ polycarboxyalkyl, optionally completely or partially ionised with at least one cation; sulpho group,

optionally completely or partially ionised with at least one cation; thiosulpho group, optionally completely or partially ionised with at least one cation; epoxide group; glycidyl; acrylate; C_{1-30} ester; polyester consisting of from 2-200 C_{2-15} diacid and diester monomer units; and esters of inorganic acids, all alkyl chains being at least one of linear, 5 branched and comprising at least one ring.

A more preferred class of siloxane compounds comprises those of Formula I in which a, b, and c are all 1 and X, Y and Z are selected from

- 10 $-O-(CH_2)_{1-30}-$, this moiety being linear or branched;
 $-(CH_2)_{1-30}-$, this moiety being linear or branched;
 $-CH_2-CH_2-CH_2-O-CH_2-CHOH-CH_2-$;

and R, R' and R'' are independently selected from at least one of hydrogen; hydroxy; 15 polyether consisting of from 2-200 identical or different C_{2-6} oxyalkylene units, with the proviso that, if there is present more than one type of oxyalkylene unit, there shall be present at least two of each unit; C_{3-30} quaternary ammonium, optionally completely or partially ionised with at least one anion; C_{4-30} betaine; carboxyl, optionally completely or 20 partially ionised with at least one cation; sulpho group, optionally completely or partially ionised with at least one cation; thiosulpho group, optionally completely or partially ionised with at least one cation; glycidyl; and acrylate; all alkyl chains being at least one of linear, branched and comprising at least one ring.

An even more preferred class of siloxane compounds comprises those of Formula I in 25 which m and n are independently selected from 1-200, a, b, and c are all 1 and X, Y and Z are selected from

- $-O-(CH_2)_{1-12}-$;
 $-(CH_2)_{1-12}-$;
 30 $-CH_2-CH_2-CH_2-O-CH_2-CHOH-CH_2-$;

and R, R' and R'' are independently selected from at least one of hydrogen; hydroxy; polyether consisting of from 2-200 identical or different C_{2-6} oxyalkylene units, with the

proviso that, if there is present more than one type of oxyalkylene unit, there shall be present at least two of each unit; C₃₋₃₀ quaternary ammonium, optionally completely or partially ionised with at least one anion; C₄₋₃₀ betaine; carboxyl, optionally completely or partially ionised with at least one cation; glycidyl; and acrylate; all alkyl chains being
5 capable of being linear or branched.

An even more preferred class of siloxane compounds comprises those of Formula I in which m is from 1-30 and n is from 1-100, a, b, and c are all 1 and X, Y and Z are selected from

10



15 and R, R' and R'' are independently selected from at least one of hydrogen; hydroxy; polyether consisting of from 2-200 identical or different C₂₋₆ oxyalkylene units, with the proviso that, if there is present more than one type of oxyalkylene unit, there shall be present at least two of each unit; C₃₋₂₀ quaternary ammonium, optionally completely or partially ionised with at least one anion; C₄₋₁₀ betaine and carboxyl, optionally completely
20 or partially ionised with at least one cation; all alkyl chains being capable of being linear or branched.

The siloxanes hereinabove described may be any such material known to the art. Such materials are well known to the art for a variety of purposes, one of these being as
25 antifoams in various industries. The preferred materials are those where R and R' are methyl or ethyl, n is from 5-200, more preferably from 10-150 and most preferably from 40-100, and m is from 1-100, more preferably from 2-40 and most preferably from 5-10.

The two different types of siloxane units may be arranged randomly or in blocks on the
30 molecule. It is possible to utilise more than one type of moiety R''. Examples of R'' include ethylene oxide - propylene oxide copolymers of from 10 to 100 units.

The siloxanes that are useful in the present invention may either be incorporated into a dry cementitious composition, or they may be added to such a composition when it is mixed with water immediately prior to placement. The quantity required depends on the type of cement and the precise nature of the siloxane, but a typical range of weight proportions is from 0.05%-20% by weight of the weight of the cement, more preferably from 0.1-5%, even more preferably from 0.1-2% and most preferably from 0.2-1%.

In a further embodiment of the invention, the siloxane may be used in conjunction with hydrophobic, finely-divided silica. This can be added to the composition separately from the siloxane, but it is preferred that it be incorporated into the siloxane by, for example, blending or mixing. The quantity of silica can be up to 20% by weight of the siloxane, preferably no more than 10%. In a yet further embodiment of the invention, the siloxane may additionally contain emulsifier. Any suitable emulsifiers may be used in art-recognised quantities. Some commercially-available emulsifiers already contain emulsifier, so addition may be unnecessary.

In addition to the siloxane hereinabove described, there can also be added to the cementitious mix materials known to the art for the performance of particular functions, in art-recognised quantities. Such materials include (but are not limited to) plasticisers and superplasticisers, antifreeze agents, pigments, air-entraining agents, accelerators, retarders and reinforcing fibres of metal, glass or polymer.

Cementitious mixes to which the siloxanes as hereinabove described have been added exhibit superior shrinkage characteristics, leading to better aesthetic appearance, reduced permeability and superior properties with respect to durability. The invention therefore also provides a cementitious composition which includes a siloxane as hereinabove described.

The invention is further described with reference to the following non-limiting example.

A polyether siloxane ("Tego" (trade mark) 2008 MR ex Degussa AG is used) is added to a concrete mix of the following composition:

MBZ-0520

6

Portland cement 450 parts by weight

Aggregate

	0-4mm	770	"
	4-8mm	440	"
5	8-16mm	440	"

W/C ratio 0.47

This mix is subjected to the shrinkage test of German Industrial Standard DIN 52 450, along with a mix that does not contain the siloxane.


10

The results are as follows:

Age(days)		shrinkage (mm/M)	
		with siloxane	without siloxane
15	1	0	0
	3	-0.119	0.029
	7	-0.074	0.157
	10	-0.006	0.195
	14	0.057	0.225
20	28	0.082	0.349
	42	0.17	0.405
	49	0.193	0.418
	59	0.167	0.396
	70	0.244	0.48
25	80	0.271	0.503

Claims:

1. A method of reducing the drying shrinkage of a cementitious composition to which water has been added and the composition placed, comprising adding to the composition prior to placement at least one siloxane compound that is at least one of liquid and soluble in at least one of water and aqueous alkali.
2. A method according to claim 1, in which the siloxane compound selected from those that correspond to the general formula I:



where m and n are independently from 1-2000, preferably from 1-500 and more preferably from 1-200, a, b, and c are independently either 0 or 1 and X, Y and Z are selected from

- O-;
- O-(CH₂)₁₋₃₀-, this moiety being at least one of linear, branched and containing at least one ring;
- (CH₂)₁₋₃₀-, this moiety being at least one of linear, branched and containing at least one ring;
- CH₂-CH₂-CH₂-O-;
- CH₂-CH₂-CH₂-O-CH₂-CHOH-CH₂-;
- CH₂-CH₂-CH₂-O-CH₂-CHOH-CH₂-O-;
- CH₂-CH₂-CH₂-O-CH₂-CHOH-CH₂-N-;



and R, R' and R'' are independently selected from at least one of hydrogen, C₁₋₁₀₀ alkyl, C₆₋₃₀ aryl, C₇₋₃₀ aralkyl; C₇₋₃₀ alkaryl; C₁₋₃₀ hydroxyalkyl; C₃₋₂₀₀ polyhydroxyalkyl; polyether consisting of from 2-200 identical or different C₁₋₁₅ oxyalkylene units, with the proviso that, if there is present more than one type of oxyalkylene unit, there shall be present at least two of each unit; C₁₋₃₀ aminoalkyl; polyiminopolyalkylene having from 1-20 identical or different C₂₋₁₅ alkylene units; polyiminopolyoxyalkylene having from 1-20 identical or different C₂₋₁₅ oxyalkylene units; C₃₋₃₀ quaternary ammonium, optionally completely or partially ionised with at least one anion; C₄₋₃₀ betaine; carboxyl, optionally completely or partially ionised with any suitable cation; C₄₋₃₀ polycarboxyalkyl, optionally completely or partially ionised with at least one cation; sulpho group, optionally completely or partially ionised with at least one cation; thiosulpho group, optionally completely or partially ionised with at least one cation; epoxide group; glycidyl; acrylate; C₁₋₃₀ ester; polyester consisting of from 2-200 C₂₋₁₅ diacid and diester monomer units; and esters of inorganic acids, all alkyl chains being at least one of linear, branched and comprising at least one ring.

3. A method according to claim 2, in which the siloxane compound of formula I is such that a, b, and c are all 1 and X, Y and Z are selected from

- O-(CH₂)₁₋₃₀-, this moiety being linear or branched;
- (CH₂)₁₋₃₀-, this moiety being linear or branched;
- CH₂-CH₂-CH₂-O-CH₂-CHOH-CH₂-;



and R, R' and R'' are independently selected from at least one of hydrogen; hydroxy; polyether consisting of from 2-200 identical or different C₂₋₆ oxyalkylene units, with the proviso that, if there is present more than one type of oxyalkylene unit, there shall be present at least two of each unit; C₃₋₃₀ quaternary ammonium, optionally completely or partially ionised with at least one anion; C₄₋₃₀ betaine; carboxyl, optionally completely or partially ionised with at least one cation; sulpho group, optionally completely or partially ionised with at least one cation; thiosulpho group, optionally completely or partially ionised with at least one cation; glycidyl; and acrylate; all alkyl chains being at least one of linear, branched and comprising at least one ring.

4. A method according to claim 2, in which the siloxane compound of Formula I is such that m and n are independently selected from 1-200, a, b, and c are all 1 and X, Y and Z are selected from



and R, R' and R'' are independently selected from at least one of hydrogen; hydroxy; polyether consisting of from 2-200 identical or different C₂₋₆ oxyalkylene units, with the proviso that, if there is present more than one type of oxyalkylene unit, there shall be present at least two of each unit; C₃₋₃₀ quaternary ammonium, optionally completely or partially ionised with at least one anion; C₄₋₃₀ betaine; carboxyl, optionally completely or partially ionised with at least one cation; glycidyl; and acrylate; all alkyl chains being capable of being linear or branched.

5. A method according to claim 2, in which the siloxane compound of Formula I is such that m is from 1-30 and n is from 1-100, a, b, and c are all 1 and X, Y and Z are selected from



and R, R' and R'' are independently selected from at least one of hydrogen; hydroxy; polyether consisting of from 2-200 identical or different C₂₋₆ oxyalkylene units, with the proviso that, if there is present more than one type of oxyalkylene unit, there shall be present at least two of each unit; C₃₋₂₀ quaternary ammonium, optionally completely or partially ionised with at least one anion; C₄₋₁₀ betaine and carboxyl, optionally completely or partially ionised with at least one cation; all alkyl chains being capable of being linear or branched.

6. A method according to any one of claims 1-5, in which finely-divided silica is added to the cementitious composition.
7. A cementitious composition with reduced drying shrinkage, prepared by a method
5 according to any one of claims 1-6.
8. A cementitious composition according to claim 7, in which the composition additionally contains finely-divided silica.

ABSTRACT

- 5 A method of reducing the drying shrinkage of a cementitious composition to which water has been added and the composition placed, comprising adding to the composition prior to placement at least one siloxane compound that is at least one of liquid and soluble in at least one of water and aqueous alkali.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.